

IN THE U.S. PATENT AND TRADEMARK OFFICE

3/4 Priority
Doc.

E. Willis

4-5-00

Applicant(s): HOLLANDS, Peter Joseph; ELLENKAMP, Hendrik Willem
Application No.: Group:
Filed: January 14, 2000 Examiner:
For: INKJET PRINTHEAD



LETTER

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

January 14, 2000
0142-0309P

Sir:

Under the provisions of 35 USC 119 and 37 CFR 1.55(a), the applicant hereby claims the right of priority based on the following application(s):


<u>Country</u>	<u>Application No.</u>	<u>Filed</u>
EUROPEAN PATENT OFFICE	99200195.8	01/22/99

A certified copy of the above-noted application(s) is(are) attached hereto.

If necessary, the Commissioner is hereby authorized in this, concurrent, and future replies, to charge payment or credit any overpayment to deposit Account No. 02-2448 for any additional fees required under 37 C.F.R. 1.16 or under 37 C.F.R. 1.17; particularly, extension of time fees.

Respectfully submitted,

BIRCH, STEWART, KOLASCH & BIRCH, LLP

By: 
RAYMOND C. STEWART
Reg. No. 21,066

P. O. Box 747
Falls Church, Virginia 22040-0747

#22463

Attachment
(703) 205-8000
/djm



**Eur päisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets** 1 of 1

HOLLANDS et al
142-309 P
BSKB
(703)205-8000

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

99200195.8

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

Aslette Fiedler

A. Fiedler

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

19/07/99



**Eur päisches
Patentamt**

**Eur pean
Patent Office**

**Office européen
des brevets**

**Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation**

Anmeldung Nr.:
Application no.:
Demande n°: **99200195.8**

Anmeldetag:
Date of filing:
Date de dépôt: **22/01/99**

Anmelder:
Applicant(s):
Demandeur(s):
Océ-Technologies B.V.
5914 CC Venlo
NETHERLANDS

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Inkjet printhead

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

B41J2/14

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: **AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE**
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

Océ-Technologies B.V., of Venlo

22 01 1999

Inkjet printhead

- 5 The invention relates to an ink jet printhead comprising a channel plate having a plurality of ink channels etched into at least one surface thereof, actuators respectively associated with each of the ink channels for pressurizing ink contained in the ink channels, and means defining an ink reservoir communicating with the ink channels. The invention further relates to a process for manufacturing such a printhead.
- 10 An example of a conventional printhead of this type is described in EP-A-0 671 372. The ink channels are arranged side-by-side in one surface of the channel plate and extend in parallel to one another with narrow spacings formed therebetween. Each ink channel converges into a nozzle at one end thereof, so that an array of nozzles is formed, by which a plurality of ink droplets can be expelled simultaneously by energizing the
- 15 actuators respectively associated with the ink channels. For a high-resolution printer, it is required that the spacings between the adjacent nozzles are made as small as possible, and, accordingly, the ink channels and the wall portions separating them must have very small dimensions in the width direction.
- The ink reservoir defining means and the channel plate are formed by a one-piece
- 20 substrate made of a material such as silicon, in which the ink channels can be formed by photo-lithographic etching. This has the advantage that the minute structures of the ink channels and the nozzles can be formed with high accuracy. Cavities defining the ink reservoir and supply passages connecting the ink reservoir to each of the ink channels are formed directly in the silicon substrate by etching away appropriate
- 25 portions of the substrate.
- As an alternative, it has been proposed to form the channel plate and the ink reservoir defining means by a one-piece block of graphite. In this case, however, the ink channels must be cut into the surface of the channel plate, and the process of forming the minute structures of the ink channels and nozzles becomes more cumbersome or a graphite
- 30 with a very small grain size must be used which makes the inkjet printhead expensive. It is an object of the present invention to provide an ink jet printhead of the type indicated in the preamble, which can be manufactured at low costs and in which the ink channels can nevertheless be formed reproducibly with high accuracy.
- According to the invention, this object is achieved by the feature that the ink reservoir
- 35 defining means are formed by a base member made of a material different from that of

the channel plate.

As a result, it is not necessary to form the comparatively large volume of the ink reservoir in a time-consuming etching process, and the rather bulky member of the printhead in which the ink reservoir is formed can be manufactured at low costs by molding, sintering or machining a rather inexpensive material such as graphite or ceramic in a relatively grainy form. Only the comparatively small volume of the channel plate is made from a more expensive material such as silicon, fine grain graphite ceramics in which the fine structures of the ink channels, and, as the case may be, the nozzles, can be formed with high accuracy in an etching or mechanical process in which only a little amount of material has to be removed. Thus, not only the costs for the material but also the costs for the manufacturing process can be reduced significantly. More specific optional features of the invention are indicated in the dependent claims.

In a preferred embodiment the channel plate and the member defining the ink reservoir are manufactured as separate members and are then buttingly assembled together and fixed to one another, e.g. by bonding, so that fluid connections between the ink reservoir and each of the ink channels are established. In this case, the ink channels can be etched or machined before the channel plate and the ink reservoir defining member are assembled, so that the apparatus needs to have only small dimensions and/or a large number of channel plates can be etched simultaneously. One suitable manufacturing process is claimed in claim 7.

As an alternative, it would also be possible that the etchable material, e.g. silicon, is directly deposited on a portion of the member defining the ink reservoir, and then the ink channels are formed by etching.

In a preferred design of an ink jet printhead the nozzles are arranged in two parallel rows. In this case, the ink channels associated with the respective rows of nozzles can either be formed in opposite surfaces of a single channel plate or can be formed in the surfaces of separate channel plates sandwiched with a portion of the ink reservoir defining member. In the latter case, a large area of contact between the channel plates and the ink reservoir defining member is achieved, and, accordingly, there is a good thermal contact between the ink reservoir defining member and the channel plates, which is particularly advantageous in case of a hot-melt printhead in which the ink contained in the ink reservoir and the ink channels needs to be liquified by heating. Preferred embodiments of the invention will now be explained in conjunction with the drawings in which:

Fig. 1 is a longitudinally sectioned perspective explosion view of a printhead

according to the invention;

Fig. 2 is an enlarged cross-sectional view of a lower portion of the printhead shown in figure 2, the cross-section being taken along the line II-II in figure 1; and

Fig. 3 is a cross-sectional view of a printhead according to a modified embodiment.

- 5 As is shown in figures 1 and 2, an ink jet printhead according to the invention has a symmetric structure and comprises as main components a base plate 10 made of graphite or ceramic and a channel plate 12 made of an etchable material, preferably a semiconductor material such as silicon. The channel plate 12 has opposite lateral surfaces in which a plurality of parallel, vertically extending ink channels 14 are formed
- 10 by etching. Each ink channel 14 is converged to form a nozzle 16 (figure 2) at the lower end thereof and is open at its top end. The open lateral sides of the ink channels 14 and the nozzles 16 are covered by a flexible sheet 18 made of the same material as the channel plate 12 and firmly bonded thereto. An actuator block 20 is bonded to the outer surface of each sheet 18. The actuator block 20 is made of a piezoelectric ceramic
- 15 material and has a comb-like structure forming a plurality of parallel, vertically extending piezoelectric fingers 22 and is provided with electrodes (not shown) associated with each of the fingers 22. A flexible lead foil 24 is attached to the outer surface of each of the actuator blocks 20 and is formed with electric leads for individually energizing the piezoelectric fingers 22.
- 20 The actuator blocks 20 are protected by a cap 26 fitted over the lower end of the channel plate 12 and bonded to the lower edges of the sheets 18 and to the end faces 28 of the channel plate 12.

The base member 10 is a plate-like member having a comparatively thick top portion 30 in which an ink reservoir 32 and a receptacle 34 for a filter element (not shown) are

25 formed. A lower portion 36 of the base plate 10 has a reduced thickness and width and is formed with a recess 38 extending along its lower edge. Ink supply passages 40 are symmetrically formed in the cross section of the lower portion 36 of the base plate. The ink supply passages 40 are in fluid communication with the ink reservoir 32 and are open to the bottom of the recess 38.

- 30 As is shown in figure 2, the channel plate 12, the flexible sheets 18 and the actuator blocks 20 form a unit which is fitted to the lower edge of the base plate 10, so that the top portions of the channel plate 12 and the sheets 18 project into the recess 38. The thickness of the channel plate 12 is larger than the thickness of a web portion 42 of the base plate 10 separating the ink supply passages 40. Thus, the open ends of the ink
- 35 channels 14 are in fluid communication with the ink reservoir 32 via the ink supply

passages 40.

The outer surfaces of the sheets 18 projecting upwardly beyond the actuator blocks 20 are bonded to the lateral walls of the recess 38 by means of an adhesive 44, so that the ink supply passages 40 are sealed and the channel plate 12 is held in firm engagement with the web portion 42 of the base plate.

The flexible lead foils 24 are led-out on either side of the base plate 10 and are protected against tensile forces by clamping bars 46 which, together with mounting blocks 48 (figure 1) form a frame surrounding the lower portion 36 of the base plate.

In the shown embodiment, the printhead is a hot-melt ink jet printhead, and, as is known per-se, heating means (not shown) are provided for heating the base plate 10 so that the hot-melt ink contained in the ink reservoir 32, the ink supply passages 40 and the ink channels 14 is kept in the liquid state. If desired, electric auxiliary heating means can be formed in the channel plate 12, for example by appropriately doping the silicon material so that resistance heating layers are formed.

When the printhead is operated, electric signals are supplied to the individual piezoelectric fingers 22 via the lead foils 24, so that the piezoelectric fingers perform expansion and retraction strokes towards and away from the associated ink channel 14, so that the sheet 18 covering this ink channel is flexed and the liquid ink contained in the ink channel is pressurized and an ink droplet is jetted-out through the nozzle 16.

As can be seen in figures 1 and 2, the amount of bulk material needed for the base plate 10 is considerably larger than the amount of material needed for the channel plate 12. It is accordingly an important advantage of the invention that only the comparatively small channel plate 12 needs to be made of an expensive material such as silicon. In the manufacturing process, the pattern of ink channels 14 and nozzles 16 can be

formed with high precision in both lateral surfaces of the channel plate 12 by using photo-lithographic etching techniques. Then, the ink channels are covered with the flexible sheets 18 and the actuator blocks 20 are secured thereto by bonding. The fact that, at this stage, the channel plate 12 is not yet fitted to the base plate 10, facilitates the fine adjustment of the piezoelectric fingers 22 of the actuator blocks relative to the ink channels 14. Finally, the unit formed by the channel plate, the flexible sheets 18 and the actuator blocks 20 is fitted to the base plate 10 and secured thereto by bonding.

Figure 3 shows a modified embodiment in which the web portion 42 of the base plate 10, instead of forming the recess 38 shown in figure 2, is extended to form a support plate 48 sandwiched between two separate channel plates 12. In this embodiment, the amount of silicon material required for forming the two channel plates is even smaller

than in the case of figure 2, and each channel plate forms only one row of ink channels 14. The thickness of the support plate 48 is preferably smaller than that of the web portion 42, so that the channel plates can be abutted against a shoulder formed between the support plate 48 and the web portion 42. The flexible sheets 18 are in this case made from slightly thicker plates which are in abutting engagement with the lower edge of the base plate 10 on either side of the projecting support plate 48 and from which a central portion has been etched away in order to accommodate the actuator blocks 20 and to provide the required flexibility.

The channel plates 12 are secured to the surfaces of the support plate 48 by means of an adhesive which provides for a good thermal contact between the base plate 10 and the channel plates.

Although only specific embodiments of the invention have been described above, it will be clear for a person skilled in the art that various modifications and changes can be made within the scope of the appended claims.

It is possible to use for the base member (10) and the channel plate (12) graphite. In that situation a graphite with carbon particles having a grain size greater than 10 μm is used for the base member (10) and for the channel plate (12) a graphite with carbon particles having a grain size smaller than 10 μm , preferably smaller than 3 μm .

22 01. 1999

CLAIMS

1. Ink jet printhead comprising a channel plate (12) having a plurality of ink
5 channels (14) etched into at least one surface thereof, actuators (22) respectively
associated with each of the ink channels for pressurizing ink contained in the ink
channels, and means (10) defining an ink reservoir (32) communicating with the ink
channels, characterized in that said ink reservoir defining means are formed by a base
member (10) made of a material different from that of the channel plate (12).

10 2. Ink jet printhead according to claim 1, wherein the channel plate (12) is held in
butting engagement with a surface of the base member (10) in which an ink supply
passage (40) is formed for establishing fluid communication between the ink reservoir
(32) and the ink channels (14).

15 3. Ink jet printhead according to claim 1 or 2, wherein the channel plate (12) is
fixed to the base member (10) by means of an adhesive.

4. Ink jet printhead according to any of the preceding claims, wherein the base
member (10) is made of graphite.

5. Ink jet printhead according to any of the preceding claims, wherein the channel
plate (12) is made of silicon.

20 6. Ink jet printhead according to any of the preceding claims, wherein a portion of
the base member (10) forms a support plate (48) sandwiched between two separate
channel plates (12).

25 7. Method of manufacturing an ink jet printhead according to any of the preceding
claims, wherein the channel plate (12), a flexible sheet (18) covering open sides of the
ink channels (14) and an actuator block (20) forming the actuators (22) are assembled
and fixed to each other to form a unit which is then fitted to the base member (10).



22 01. 1999

ABSTRACT

Ink jet printhead comprising a channel plate (12) having a plurality of ink channels (14) etched into at least one surface thereof, actuators (22) respectively associated with each of the ink channels for pressurizing ink contained in the ink channels, and means (10) defining an ink reservoir (32) communicating with the ink channels, wherein that said ink reservoir defining means are formed by a base member (10) made of a material different from that of the channel late (12).

10 (Fig. 3)

22 01. 1999

Fig. 1**Fig. 2****Fig. 3**